

Professional Finishing proSpray 3.34 ProSpray Airless piston pumps Perfectly matched performance categories **Innovative product features Proven professional quality**



INNOVATIVE TECHNOLOGY

The 3rd piston pump generation from WAGNER convinces thanks to perfectly matched performance categories and a wide range of applications both indoors and outdoors. WAGNER offers the right ProSpray piston pump for every area of application, from lacquers and emulsions right up to highly viscous materials on small and large construction sites.

			Мо	del	
Materials	Object size	PS 3.21	PS 3.25	PS 3.31	PS 3.39
Release agents, oils, undercoats, primers, fillers, synthetic resin-based paints, acrylic paints recommended nozzle size: FF 0.008" - 0.014"	up to 200 m ²				
	200 m ² - 800 m ²				
	more than 800 m ²				
Emulsion paints, latex paints recommended nozzle size: 0.017" - 0.027"	up to 200 m ²				
	200 m ² - 800 m ²				
	more than 800 m ²				
Anti-corrosive agents, flame retardants, fabric adhesives recommended nozzle size: 0.021" - 0.031"	up to 200 m ²				
	200 m ² - 800 m ²				
	more than 800 m ²				
Airless stoppers recommended nozzle size: 0.027" - 0.039"	up to 200 m ²				
	$200 \text{m}^2 - 800 \text{m}^2$				
	more than 800 m ²				





Professional Finishing

advantages...



Clean storage of the flexible suction system, EasyGlide and EasyClean.



The pressure gauge gives precise information about the set spray pressure.

...which convince



Swivel joint on the flexible suction system, removable without tools.



The inlet valve depressor guarantees high operating reliability.
One press of a button and the valve is free.





PS 3.21

Delivery package PS 3.21 Airless Spraypack

- + ProSpray 3.21 SKID basic unit, 110 V / 50 Hz
- + HP hose DN6-ND270, 15 m, yellow
- + Airless gun AG 08, 250 bar, incl. TradeTip 2 nozzle holder
- + 2SpeedTip nozzle D7 113/417

Article-No.	2311 375
Technical Data	PS 3.21
Max. delivery rate	2.0 l/min
Max. nozzle size	0.023"
Max. operating pressure	230 bar
Motor output	0.65 kW
Weight	16 kg

PS 3.25

Delivery package PS 3.25 HR Airless Spraypack

- + ProSpray 3.25 HR basic unit on cart, 110 V / 50 Hz
- + HP hose DN6-ND270, 15 m, yellow
- + Airless gun AG 08, 250 bar, incl. TradeTip 2 nozzle holder
- + 2SpeedTip nozzle D7 113/417

Article-No.	2311 378
Technical Data	PS 3.25
Max. delivery rate	2.6 l/min
Max. nozzle size	0.027"
Max. operating pressure	230 bar
Motor output	1.1 kW
Weight	25.5 kg

advantages...



Fast change of the container and easy cleaning thanks to the tilting cart.



The microprocessor based electronic system controls and regulates all functions.

...which convince



Quick change of the suction system without tools.



The low position of the inlet valve of the PS 3.39 improves the suction power for high viscosity materials.





PS 3.31

Delivery package PS 3.31 Airless Spraypack

- + ProSpray 3.31 HR basic unit, 110 V / 50 Hz
- + HP hose DN6-ND270, 15 m, yellow
- + Airless gun AG 08, 250 bar, incl. TradeTip 2 nozzle holder
- + 2SpeedTip nozzle D20 115/421

Article-No.	2311 380
T 1 1 10 .	DC 2 24
Technical Data	PS 3.31
Max. delivery rate	3.8 l/min
Max. nozzle size 1/2 Guns	0.032"/0.021"
Max. operating pressure	230 bar
Motor output	1.7 kW
Weight	38 kg

PS 3.39


Delivery package PS 3.39 Airless Spraypack

- + ProSpray 3.39 HR basic unit, 110 V / 50 Hz
- + HP hose DN10-ND230, NPSM 3/8", 15 m, yellow
- + HP hose wand DN5-ND270, NPS 1/4", 1 m
- + Airless gun AG 14, NPS 1/4", incl. TradeTip 2 nozzle holder
- + 2SpeedTip nozzle D20 115/421

Article-No.	2311 382
Technical Data	PS 3.39
Max. delivery rate	5.0 l/min
Max. nozzle size 1/2 Guns	0.039"/0.026"
Max. operating pressure	230 bar
Motor output	2.68 kW
Weight	44 kg

The 3rd ProSpray generation with convincing product features





deadband control, SlowMotion function and FrequentClean guarantee trouble-free work and quick cleaning.



The **innovative brushless DC motor** requires no maintenance. Thanks to its compact dimensions it is light in weight. Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure.



Maintenance made easy. With the push of a button the piston is oiled and thus the packings are conserved. The "Easy Glide" machine oil can be refilled easily. It forms a protective film around cylinder and piston and protects the unit against premature wear.



The new practical, **self-adjusting packings** lead to less wear and are easy to change. They have a service life up to 50% longer than the current packings which means significantly lower maintenance costs.



The high pressure filter is **easily accesible** and quick to clean. The additional filtering protects against time-consuming, paint blockages and so facilitates the work. Three different filter inserts (fine, medium, coarse) ensure an optimal match with the material.







Guarantee-Offensive!

With each newly purchased professional paint spraying unit you will now get a 3 year manufacturer's guarantee from WAGNER.

Ensure two additional years of guarantee with your Online registration. This is unique in the industry! Because: We are convinced of our professional quality. Take our word for it!

ProSpray accessories



Together with the unit and the nozzle, the gun is the centrepiece in every spraying operation. The optimum spray jet adjustment possibilities give you perfect results every time.

0296 393 Airless gun AG 08 (F-thread) incl. nozzle and nozzle holder

0502 168 Airless gun AG 14 (F-thread) incl. nozzle and nozzle holder

Paint rolling with Airless technology: The Airless system automatically transports the coating material from the drum to the paint roller. Convenient and efficient working without carrying cans and dipping into the drum.

0345 010 InlineRoller complete with hose in plastic box.

Nozzles



TradeTip2 nozzles offer a wide range of uses for optimum adjustment to the project in question, and are available in various types and sizes: from 0.007" to 0.067" and with spraying angles from 10° to 120° (see the current compass and nozzles manual).

TipClean

InlineRoller



Contactless cleaning and clean storage.

0097 108 Container incl. special cleaner Special cleaner for TipClean (1 litre)



The nozzle innovation from WAGNER. Now you can work even faster and more flexibly. With the new 2SpeedTip nozzles you can swap between two nozzle sizes with just one twist. The nozzle is available in various nozzle combinations (see current brochure).

Pole guns



Pole guns save using ladders and scaffolding.

0296 443 Pole gun 120 cm, 1/4" nozzle holder, F-thread 11/16"

Pole gun 200 cm, 1/4" nozzle holder, F-thread 11/16"



Gun filters prevent nozzle blockages. (Each pack contains 10 pcs.).

Extra fine filter insert, red 0097 023 Fine filter insert, yellow

Medium filter insert, white 0097 024

Large volume container



For the application of large quantities we recommend using the mobile, solvent-resistant, and very easily cleaned large volume container with a capacity of 100 litres. Low own weight.

Large volume container, complete incl. lid



... the cleanest solution. The patented accessory from WAGNER for air-tight closure of the suction tube.

2306 987 PumpRunner

High pressure hoses



A wide choice of material hoses is available for various material applications and action radii.

HP hose DN6-ND270, 1/4", 15 m, yellow

HP hose DN6-ND270, 9984 575 1/4", 30 m, yellow

